

The liquid-tight washing area

ECO SEALS®

ECOseals b.v.

PO Box19
5400 AD UDEN NL

Chamber of Commerce:5852811
VAT: NL853079079B01

info@ecoseals.eu
www.ecoseals.eu



Liquid tight provision of strong composite, modular, movable, chemical resistant en durable.



Liquid tight provision of strong **composition, modular, movable, chemical resistant** and durable.



Technical specifications:

- Above ground setup and therefore mobile
- Life expectancy > Long
- Modular construction of floor plates, up to desired surface
- Easy transport, container size, 10 x lighter than concrete
- Traffic class 600 (for 60 tonnes of traffic, with an axle load of up to 20 tonnes)
- Durable resistant to static and dynamic mechanical loads on bonded foundation
- Durable resistant to thermal, physical and chemical influences
- Possibly with screen walls, (washing) installation, HD cleaner etcetera
- Including above-ground sludge trap / separator and waste water pump frost-free if required
- Integrated drainage system with trouble-free sludge handling
- Including in NL an independent inspection and VVW certificate
- Use of an existing paving as a foundation basis or fully load-bearing strong foundation
- No digging, cunet or piling or heavy foundation required
- CO2 footprint is neutral compared to a concrete floor
- Design according to "cradle to cradle" principle
- ECOseals floor meets the circularity requirements of the current environmental policy

The mobile liquid-tight composite floor has special qualities for industrial cleaning. The high chemical resistance speaks for itself and is above all very robust. An extremely professional facility with large capacity, suitable for almost every situation. This mobile concept is based on our sustainable, liquid-tight composite floor with many additional features.